

# RENEGADE EXPLOIT

## SPECIFICATIONS

Frame	Jamis Size Specific Design frame geometry, Reynolds 631 double-butted chromoly main tubes, 44mm head tube for tapered fork, threaded BB shell, 12x142 Jamis MTS (Modular Thru-axle System), flat mount disc brake mounts, top tube mounted full cable housing, dropper post cable guides, 3 waterbottle mounts, rack and fender eyelets, clearance for 700x42c and 650x47c tires.
Fork	Jamis Adventure ECO mono-coque carbon composite, 12mm Jamis MTS (Modular Thru-axle System) with stainless interface and carbon dropouts, tapered steerer with 1.5" hollow formed crown, flat mount disc brakes with internal cable routing, exposed fender, lowrider and water bottle eyelets
Headset	FSA Orbit ITA B Internal/External, 1.5 - 1 1/8"
Wheels	WTB i23 STS disc rims with TCS (UST Tubeless Compliant System), 32H, Formula alloy Centerlock sealed bearing hubs with front 12mm/rear 12x142 thru-axle and 14g black stainless steel spokes
Tires	Clement X Plor MSO, 650 x 36c (44-48) 700 x 36c (51-61), 30TPI with protection belt
Derailleurs	Shimano 105 RD-5800 GS rear and 105 FD-5801 with 28.6mm alloy clamp
Shiftlevers	Shimano RS505 Dual Control STI, 22-speed
Chain	Shimano CN-HG601
Cassette	Shimano 105 11-speed, 11-32T
Crankset	Shimano 105 FC-5800 compact double, 50/34T, 165mm (44/48), 170mm (51), 172.5mm (54/56), 175mm (58/61)
BB Set	Shimano SM-BBR60
Pedals	N/A
Brakeset	Shimano BR-RS505 hydraulic disc brakes with resin pads, Centerlock Ice Tech 160mm rotors and Shimano ST-RS505 Dual Control STI levers
Handlebar	Ritchey Evomax Comp, 6061 aluminum, 73 reach, 120 drop with 12° flare, 31.8 x 400 (44) 420 (48-51) 440mm (54-56), 460mm (56-61)
Stem	Ritchey 4-Axis 3D forged 6061 alloy, 6" x 70mm (44), 80mm (48/51), 90mm (54/56), 110mm (58/61)
Crips	Fizik Microtex Superlight Soft Touch with gel inserts
Seat Post	Jamis carbon fiber micro-adjust, 27.2 x 330mm with chromo seat pin
Saddle	Selle Royal Seta S1 with integrated clip system
Sizes	44 and 48 650, 51, 54, 56, 58, 61cm 700c
Color	
Weight	23.75 lbs



## TECH FEATURES

REYNOLDS

SSD  
SIZE SPECIFIC DESIGN

ECO

## UPGRADES/CHANGES FROM PREVIOUS MODEL

Jamis Size Specific Design 44/48 650 frame geometry

Shimano upgraded RD-5801 FD

## REASONS TO UPGRADE FROM RENEGADE EXPAT

Renegade Adventure Reynolds 631 double-butted chromoly frame

Shimano 105 22-speed group including crankset

Shimano BR-RS505 hydraulic disc brakes

WTB i23 STS disc rims with TCS (UST Tubeless Compliant System)

Formula sealed bearing Centerlock hubs

## GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
44	19.76 / 502	71°	73°	16.69 / 424	38.38 / 975	1.97 / 50	2.20 / 56.0	3.86 / 98	28.15 / 715	19.49 / 495	13.82 / 351
48	20.35 / 517	71°	73°	16.69 / 424	39.05 / 992	1.97 / 50	2.14 / 54.5	4.72 / 120	28.82 / 732	20.27 / 515	14.17 / 360
51	20.98 / 533	71°	73°	16.81 / 427	39.57 / 1005	2.09 / 53	2.89 / 73.5	3.94 / 100	29.88 / 759	20.98 / 535	14.53 / 369
54	21.69 / 551	71.5°	73°	16.93 / 430	40.27 / 1023	2.09 / 53	2.83 / 72.0	5.20 / 132	31.10 / 790	22.24 / 565	14.88 / 378
56	22.44 / 570	71.5°	73°	16.93 / 430	41.02 / 1042	2.09 / 53	2.83 / 72.0	6.42 / 163	31.93 / 811	23.42 / 595	15.24 / 387
58	23.07 / 586	72°	73°	16.93 / 430	41.38 / 1051	1.97 / 50	2.77 / 70.5	7.40 / 188	32.87 / 835	24.41 / 620	15.59 / 396
61	23.66 / 601	72.5°	73°	17.20 / 435	41.97 / 1066	1.97 / 50	2.77 / 70.5	8.15 / 207	33.70 / 856	25.20 / 640	15.94 / 405